

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)



## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : FORK OIL EXP M/H 15W  
Product code : 31500

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Fluid for fork

### 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL  
Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE  
Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .  
Email : motul\_hse@motul.fr

### 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

### Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336  
Ireland : +353 1 8092566  
UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671  
24 hours a day, 7 days a week

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

### 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard statements :

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P273 Avoid release to the environment.

Precautionary statements - Disposal :

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European CHemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64742-62-7 EC: 265-166-0 REACH: *01-2119480472-38		L	25 $\leq$ x % < 50
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED			

CAS: 112-90-3 EC: 204-015-5 REACH: *  (Z)-OCTADEC-9-ENYLAMINE	GHS07, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Asp. Tox. 1, H304 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 <= x % < 1
CAS: 128-39-2 EC: 204-884-0 REACH: 01-2119490822-33  2,6-DI-TERT-BUTYLPHENOL	GHS07, GHS09 Wng Skin Irrit. 2, H315 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 1
CAS: 34140-91-5 EC: 251-846-4 REACH: *  OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3 -DIAMINE	GHS07, GHS09, GHS08 Wng Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 10		0 <= x % < 1

(Full text of H-phrases: see section 16)

#### Information on ingredients :

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.  
NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

#### In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

#### In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

#### In the event of swallowing :

Seek medical attention, showing the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

### 5.1. Extinguishing media

#### Suitable methods of extinction

Dry agent, foam, carbon dioxide.

#### Unsuitable methods of extinction

High volume water jet

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.  
Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

## 5.3. Advice for firefighters

No data available.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.  
Spilled product may make surfaces slippery.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Avoid contact with eyes.

No special precaution apart from the observance of hygiene rules

#### Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure good ventilation at the workplace

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Do not breathe fumes, vapour, spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

#### Storage

Keep out of reach of children.

#### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

No data available.

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Dermal contact.  
Long term systemic effects.  
2.77 mg/kg de poids corporel/jour

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
19.6 mg de substance/m3

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Consumers.**

Dermal contact.  
Long term systemic effects.  
2.77 mg/kg de poids corporel/jour

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Long term systemic effects.  
19.6 mg de substance/m3

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Man exposed via the environment.**

Inhalation.  
Long term systemic effects.  
5.8 mg de substance/m3

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

**Final use:**

Exposure method:  
Potential health effects:  
DMEL :

**Workers.**

Inhalation.  
Long term local effects.  
0.38 mg de substance/m3

**Predicted no effect concentration (PNEC):**

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Environmental compartment:  
PNEC :

Soil.  
38.9 µg/kg

Environmental compartment:  
PNEC :

Fresh water.  
0.45 µg/l

Environmental compartment:  
PNEC :

Sea water.  
0.045 µg/l

Environmental compartment:  
PNEC :

Intermittent waste water.  
4.5 µg/l

Environmental compartment:  
PNEC :

Fresh water sediment.  
0.196 mg/kg

Environmental compartment:  
PNEC :

Marine sediment.  
0.0196 mg/kg

Environmental compartment:  
PNEC :

Waste water treatment plant.  
10 mg/l

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Environmental compartment:  
PNEC :

Soil.  
10 mg/kg

Environmental compartment:  
PNEC :

Fresh water.  
0.00026 mg/l

Environmental compartment:  
PNEC :

Sea water.  
0.00026 mg/l

Environmental compartment:

Intermittent waste water.

PNEC :	0.55 mg/l
Environmental compartment:	Fresh water sediment.
PNEC :	0.1794 mg/kg
Environmental compartment:	Marine sediment.
PNEC :	0.01794 mg/kg

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.  
Personnel shall wear regularly laundered overalls.

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.  
Store personal protective equipment in a clean place, away from the work area.  
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.  
Use eye protectors designed to protect against liquid splashes  
Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.  
After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state :	Fluid liquid.
Color:	Amber

#### Important health, safety and environmental information

pH :	Not relevant.
Flash Point Interval :	FP > 100°C.
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Viscosity :	58.0 mm <sup>2</sup> /s à 40°C

### 9.2. Other information

No data available.

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Keep away from heat and from sources of ignition  
Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Strong oxidants  
Acids

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### SECTION 11 : TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

No data available.

##### 11.1.1. Substances

###### Acute toxicity :

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Inhalation route (Dusts/mist) : LC50 = 5.53 mg/l  
Species : Rat

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)

Oral route : LD50 >= 2000 mg/kg  
Species : Rat  
OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode de la classe de toxicité aiguë)

Dermal route : LD50 > 2000 mg/kg  
Species : Rat  
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Oral route : LD50 > 5000 mg/kg  
Species : Rat

Dermal route : LD50 > 5000 mg/kg  
Species : Rabbit

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Oral route : 300 < LD50 <= 2000 mg/kg  
Species : Rat

###### Skin corrosion/skin irritation :

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Irritation : No observed effect.  
Average score < 1.5  
Species : Rabbit  
Duration of exposure : 72 h

###### Serious damage to eyes/eye irritation :

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Iritis : Average score = 0  
Species : Rabbit  
Duration of exposure : 48 h

Conjunctival redness : Average score = 0.33  
Species : Rabbit  
Duration of exposure : 48 h

###### Respiratory or skin sensitisation :

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Guinea Pig Maximisation Test (GMPT) : Non-sensitiser.

###### Germ cell mutagenicity :

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

No mutagenic effect.

**Carcinogenicity :**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)  
Species : Mouse

**Reproductive toxicant :**

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)  
No toxic effect for reproduction

**11.1.2. Mixture****Skin corrosion/skin irritation :**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

**Serious damage to eyes/eye irritation :**

Mild eye irritation

**Aspiration hazard :**

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."  
May cause lung damage if swallowed

 **Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 140-88-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity****12.1.1. Substances**

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Fish toxicity :

0.01 < LC50 <= 0.1 mg/l

Factor M = 10

Species : Pimephales promelas

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :

0.01 < EC50 <= 0.1 mg/l

Factor M = 10

Species : Daphnia magna

OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity :

0.01 < ECr50 <= 0.1 mg/l

Factor M = 10

Species : Desmodesmus subspicatus

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)

Fish toxicity :

LC50 = 0.13 mg/l

Factor M = 10

Species : Danio rerio

Duration of exposure : 96 h

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity :

EC50 = 0.14 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity :

ECr50 = 0.041 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Fish toxicity :

LC50 >= 1.4 mg/l

Duration of exposure : 96 h

NOEC = 0.43 mg/l  
Duration of exposure : 14 jours

Crustacean toxicity :  
EC50 = 0.45 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

Algae toxicity :  
ECr50 = 1.2 mg/l  
Duration of exposure : 72 h

### 12.1.2. Mixtures

Fish toxicity : Harmful.  
10 < LC50 <= 100 mg/l

## 12.2. Persistence and degradability

### 12.2.1. Substances

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)

Biodegradability : Rapidly degradable.

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Biodegradability : Rapidly degradable.

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Biodegradability : Rapidly degradable.



### 12.2.2. Mixtures

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

## 12.3. Bioaccumulative potential

### 12.3.1. Substances

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Bioaccumulation : BCF >= 500.

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS: 64742-62-7)

Octanol/water partition coefficient : log K<sub>ow</sub> > 3

## 12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

## 12.5. Results of PBT and vPvB assessment

No data available.

## 12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.



## German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 3 : Extremely hazardous for water.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.



**Soiled packaging :**

Empty container completely. Keep label(s) on container.  
Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

- 14.1. UN number  
-
- 14.2. UN proper shipping name  
-
- 14.3. Transport hazard class(es)  
-
- 14.4. Packing group  
-
- 14.5. Environmental hazards  
-
- 14.6. Special precautions for user  
-

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

**- Container information:**

No data available.

**- Particular provisions :**


No data available.

**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 3 : Extremely hazardous for water.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Abbreviations :**

DNEL : Derived No-Effect Level

DMEL : Derived Minimal Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.