

SELFOIL

SEMI-SYNTHETIC

OPTION :




ESSENTIAL



API TC / JASO FC

SELF OIL is a semi-synthetic 2-stroke engine oil. Compatible with separate or premix lubrication engines with carburettor or injector, it ensures optimal lubrication. Contains: Mixture of: (bis(2-hydroxy-5-tetra-proenylphenylmethyl) methylamine)dicalcium dihydroxide; (tris(2-hydroxy-5-tetra-proenylphenylmethyl) methylamine)tri-calcium tri-hydroxide; poly[((2-hydroxy-5-tetraproenyl-phenylmethyl)methylamine)calcium hydroxide]. May produce an allergic reaction.



PACKING UNITS :

TECHNICAL DATA :

TEST	METHODE	TYPICAL VALUES	MEASURE UNIT
Density at 20°C	ASTM D4052	0,865	g/cm ³
Viscosity at 40°C	ASTL D445 or ASTM D7279	60	Mm ² /s
Viscosity at 100°C	ASTL D445 or ASTM D7279	9,3	Mm ² /s
Viscosity Index (VIE)	ASTM D2270	135	-
Pour point	ASTM D97	-21	°C
Flash point	ASTM D92	105	°C
TBN	ASTM D2896	1,3	mg KOH/g