



Safety data sheet

Printing date: 30.01.2014

According to 1907/2006 EEC Article 31

Version: 1

Revision: 30.01.2014

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· Trade name: **Muc Off Motorcycle Protectant + PTFE**

· Article number: 18-00000-4123 (68-35645-0100 Muc Off: 608)

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC24 Lubricants, greases, release products

· Process category

PROC11 Non industrial spraying

PROC7 Industrial spraying

· Environmental release category

ERC8a Wijdverbreid gebruik (binnen) van verwerkingshulpmiddelen in open systemen

ERC8d Wide dispersive outdoor use of processing aids in open systems

· Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Muc-Off Ltd. 1st Floor, Unit 1, Concept Office

Park, Innovation Close, Poole, Dorset

BH12 4QT, UK

Tel: +44 (0)1202 307790

Fax: +44 (0)1202 746853

E-mail: af@muc-off.com

· Further information obtainable from: Research & Development/E-mail: af@muc-off.com

· 1.4 Emergency telephone number: During normal opening hours: Tel: +44 (0)1202 307790

2 Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 1)

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms


GHS02 GHS08

Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Benzene <0.1%

Distillates (petroleum), solvent-dewaxed heavy paraffinic <0.1% Benzene

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

3.1 Substances
Additional information:

CAS: 64742-48-9 EINECS: 265-150-3 Reg.nr.: 01-2119463258-33 01-2119457273-39	Naphtha (petroleum), hydrotreated heavy Benzene <0.1% Xn R65 R66 Asp. Tox. 1, H304	50-<75%
CAS: 64742-65-0 EINECS: 265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic <0.1% Benzene Xn R65 Asp. Tox. 1, H304	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) F+ R12 Flam. Gas 1, H220; Press. Gas, H280	3-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane F+ R12 Flam. Gas 1, H220; Press. Gas, H280	3-<10%

3.2 Mixtures

Description: Active substance with propellant

Dangerous components: -

(Contd. on page 3)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 2)

· **Ingredients according to detergents guideline 648/2004/EC**

aliphatic hydrocarbons

≥ 30%

· **Additional information:**

4 First aid measures

· **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 3)

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:**

Observe official regulations on storing packagings with pressurized containers.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane (containing < 0.1 % butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL	Short-term value: 3600 mg/m ³ , 2000 ppm
	Long-term value: 1800 mg/m ³ , 1000 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol

Colour: Clear

· Odour: Sweetish

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

· Flash point: -97 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 236 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.7 Vol %

Upper: 10.9 Vol %

· Vapour pressure at 20 °C: 4 Bar

· Density at 20 °C: 0.737 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 89.2 %

Solids content: 0.4 %

· 9.2 Other information: No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 5)

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy Benzene <0.1 %

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rabbit)
Inhalative	LC50/4h	>4951 mg/l (rat)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic <0.1 % Benzene

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4h	>5 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

64742-48-9 Naphtha (petroleum), hydrotreated heavy Benzene <0.1 %

EL0 (48h)	1000 mg/l (Daphnia magna)
EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014



Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 6)

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|-----------------------|
| · 14.1 UN-Number | UN1950 |
| · ADR, IMDG, IATA | |
| · 14.2 UN proper shipping name | 1950 AEROSOLS |
| · ADR | AEROSOLS |
| · IMDG | AEROSOLS, flammable |
| · IATA | |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5F Gases. |
| · Label | 2.1 |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 |
| · Label | 2.1 |
| · 14.4 Packing group | Void |
| · ADR, IMDG, IATA | |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Gases. |
| · Danger code (Kemler): | - |
| · EMS Number: | F-D,S-U |
| · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Transport category | 2 |
| · Tunnel restriction code | D |
| · UN "Model Regulation": | UN1950, AEROSOLS, 2.1 |

GB

(Contd. on page 8)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 30.01.2014

Version: 1

Revision: 30.01.2014

Trade name: Muc Off Motorcycle Protecant + PTFE

(Contd. of page 7)

15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	75-<100

· **VOC-CH** 89.24 %

· **VOC-EU** 657.7 g/l

· **Danish MAL Code** 5-3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

· **Department issuing MSDS:** Research & Development

· **Contact:** Ing. J. Sleumer

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

· *** Data compared to the previous version altered. ***



Motorcycle Cleaner 664/667

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name Motorcycle Cleaner
Product No. 664/667

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Detergent.

1.3. Details of the supplier of the safety data sheet

Muc-Off Ltd. 1st Floor, Unit 1, Concept Office
Park, Innovation Close, Poole, Dorset
BH12 4QT, UK
Tel: +44 (0)1202 307790
Fax: +44 (0)1202 746853
E-mail: info@muc-off.com

1.4. Emergency telephone number

Emergency Contact Number (Office Hours)
+44 (0)1202 307790

Sds No. 13533

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Not classified.

2.2. Label elements

Risk Phrases
NC Not classified.

Safety Phrases
P13 Safety data sheet available for professional user on request.

2.3. Other hazards

This product does not contain any PBT or vPvB substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS		1-5%
CAS-No.: 68891-38-3	EC No.: 500-234-8	
Classification (EC 1272/2008) Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412	Classification (67/548/EEC) Xi;R38,R41.	
TETRASODIUM EDTA		1-5%
CAS-No.: 64-02-8	EC No.: 200-573-9	Registration Number: 01-2119486762-27
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H332 Eye Dam. 1 - H318	Classification (67/548/EEC) Xn;R20/22. Xi;R41.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition Comments

The data shown are in accordance with the latest EC Directives.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

Inhalation

Remove victim immediately from source of exposure. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and drink plenty of water (200-300 ml). Get medical attention if any discomfort continues.

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion

May cause stomach pain or vomiting.

Eye contact

May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture**Hazardous combustion products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Nitrous gases (NO_x).

Unusual Fire & Explosion Hazards

If heated, volume and pressure increases strongly, resulting in explosion of container.

5.3. Advice for firefighters**Special Fire Fighting Procedures**

Containers close to fire should be removed or cooled with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Do not discharge onto the ground or into water courses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Avoid spilling, skin and eye contact. Provide good ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Keep in original container.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
GLYCERINE	WEL		10 mg/m ³			

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

GLYCERINE (CAS: 56-81-5)**Ingredient Comments**

WEL = Workplace Exposure Limits

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)**DNEL**

Industry	Dermal	Long Term	Systemic Effects	2750 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	175 mg/m3
Consumer	Dermal	Long Term	Systemic Effects	1650 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	52 mg/m3
Consumer	Oral	Long Term	Systemic Effects	15 mg/kg/day

PNEC

Freshwater	0.24	mg/l
Marinewater	0.024	mg/l
STP	10000	mg/l
Sediment (Freshwater)	5.45	mg/kg
Sediment (Marinewater)	0.545	mg/kg
Soil	0.946	mg/kg

8.2. Exposure controls**Protective equipment****Respiratory equipment**

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Neoprene. EN 374

Eye protection

Wear approved safety goggles.

Other Protection

Wear suitable protective clothing as protection against splashing or contamination.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Coloured liquid.
Colour	Pink.
Odour	Characteristic.
Solubility	Soluble in water.
Relative density	1.02
pH-Value, Conc. Solution	11

9.2. Other information

Not determined.

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not determined.

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials To Avoid

Strong oxidising substances.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Nitrous gases (NO_x).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information

No information available.

Inhalation

May cause irritation to the respiratory system.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Prolonged contact may cause redness and irritation.

Eye contact

May cause temporary eye irritation. Spray and vapour in the eyes may cause irritation and smarting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.1. Toxicity

Acute Fish Toxicity

No data available.

12.2. Persistence and degradability

Degradability

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available.

12.4. Mobility in soil

Mobility:

The product is soluble in water.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Other adverse effects

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not puncture or incinerate even when empty. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

General The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

No information required.

14.2. UN proper shipping name

No information required.

14.3. Transport hazard class(es)

No information required.

14.4. Packing group

No information required.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

No information required.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No information required.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

Guidance Notes

CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date	02.06.2014
Revision	02
SDS No.	13533
Safety Data Sheet Status	Approved.
Date	27.09.2011

Risk Phrases In Full NC

R20/22	Not classified.
R38	Harmful by inhalation and if swallowed.
R41	Irritating to skin.

Hazard Statements In Full Risk of serious damage to eyes.

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.