

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML
- · Article number: 000283
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Other coatings and paints
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- *Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:
 - +31 (0)561-694400 (09:00h 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



• environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

EC number: 927-510-4	Naphtha (petroleum), hydrotreated light	25-<50
Reg.nr.: 01-2119475515-33	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 74-98-6	propane	20-<2
EINECS: 200-827-9	🊸 Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		

— Gl

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

		(Contd. of page 2)
CAS: 106-97-8	butane (containing < 0,1 % butadiene (203-450-8))	12.5-<20%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0		
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	12.5-<20%
EINECS: 200-857-2	💮 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

(Contd. of page 3)

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

· Eye/face protection Not required.

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Colourless
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 0.9 Vol % (Naphtha (petroleum), hydrotreated light)

Upper: 10.9 Vol % (74-98-6 propane)
Flash point: Not applicable, as aerosol.

• Ignition temperature: >230 °C (>446 °F) (Naphtha (petroleum),

hydrotreated light) Not determined.

Decomposition temperature: Not determined.
 pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

· Organic solvents: 92.0 %
· VOC (EC) --584.5 g/l

· VOC-EU%
 · Solids content:
 92.00 %
 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Void

(Contd. on page 6)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

		(Contd. of page 5)
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flammab	le	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

(Contd. of page 6)

Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR	1950 AEROSOLS, ENVIRONMENTALLY
ADK	HAZARDOUS
IMDG	AEROSOLS, MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
\(\frac{\Psi}{2}\)	
Class	2 5F Gases.
Label	2.1
1 1 1 1 1 1 1 1 1 1	
Class	2.1 Gases.
Label	2.1
IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDĞ, İATÂ	not regulated
14.5 Environmental hazards:	
Marine pollutant:	Yes Symbol (fish and tree)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

	(Contd. of page
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler cod	
EMS Number:	F- D , S - U
Stowage Code	SWI Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" clas
	1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk according	2. to IMO
instruments	2.
instruments Transport/Additional information:	2. to IMO
instruments Transport/Additional information: ADR	2. to IMO
instruments Transport/Additional information: ADR Limited quantities (LQ)	2. Ito IMO Not applicable.
instruments Transport/Additional information: ADR Limited quantities (LQ)	2. I to IMO Not applicable. 1L
instruments Transport/Additional information: ADR Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0
instruments Transport/Additional information: ADR Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2
-	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity Code: D Not permitted as Excepted Quantity 2 D
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2 D IL
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2 D IL Code: E0
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2 D IL Code: E0 Not permitted as Excepted Quantity
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	2. Ito IMO Not applicable. IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity 2 D IL Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity Code: E0

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 9)

Printing date 02.06.2022 Version number 157 (replaces version 156) Revision: 30.03.2022

Trade name: MOTIP CYCLING SILICONE SPRAY 400 ML

(Contd. of page 8)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

GB